

SIEMENS

SINAMICS G120P

The specialist for pumps, fans and compressors

Inverters

[siemens.com/sinamics-g120p](https://www.siemens.com/sinamics-g120p)

SINAMICS G120P

The modular inverter for pumps, fans and compressors




SINAMICS G120P has been specifically tailored to address pump, fan and compressor applications. The modular inverter comprises a Power Module and the optimum Control Unit coordinated to the particular application. Our range of Power Modules covers a power range extending from 0.37 up to 90 kW. Versions in IP20 and IP55 degrees of protection are available. SINAMICS G120P is used for simple speed adaptation as well as complex control tasks in building technology, the water industry and process industry.




SINAMICS G120P is a member of the SINAMICS family, which stands for innovative drive solutions that are fit for the future

- Wide range of power ratings from 0.12 kW up to 120 MW
- Low-voltage and medium-voltage versions available
- Standard functionality using a common hardware and software platform
- All of the drives are engineered in the same way
 - SIZER for engineering
 - STARTER for parameterizing and commissioning
- All of the drives are engineered in the same way
- High degree of flexibility and combinability

SINAMICS offers the optimum drive for every application. A real highlight: All of the drives can be engineered, parameterized, commissioned and operated in the same standard way.

Low voltage		Medium voltage
		
SINAMICS G 0.12–2,700 kW	SINAMICS S 0.12–4,500 kW	SINAMICS GM/SM/GL 0.8–120 MW

	Function	Benefit
Ruggedness – flexible, modular system for demanding ambient conditions		
	- Used for ambient temperatures from 0° up to 60°C - IP20 degree of protection - IP55 degree of protection - Coated modules	- Also used where there are high climatic loads - Space-saving mechanical design in the control cabinet, power loss is dissipated to the outside - Used without a control cabinet, i.e. wall or panel mounting - Increased ruggedness in harsh environments (humidity/dust)
	Certified according to SEMI F 47	Restart after a defined power failure
Energy saving using innovative technology		
	- Lower line harmonics as a result of the power unit with smaller DC link - Low apparent current consumption as a result of a high power factor $\lambda = 0.94 = P /S$	- Complies with standard IEC 61000-3-12 for an RSCE >250 without supplementary measures - Smaller cable cross-sections as a result of the lower current drawn
	Flux reduction in the partial load range	Power is saved in the partial load range by reducing the magnetic flux in the motor
	Hibernation mode	The inverter is shut down if it is not required in the process
User-friendly handling/simple application-specific commissioning		
	Pluggable operator panels	- Fast commissioning without expert knowledge - Display with user-friendly plain text (IOP) or two channels (BOP-2) - Minimized maintenance work
	Application support using wizards in the IOP and macros in STARTER	Prompted commissioning for applications in building technology and the water and process industries
	Integrated USB port (plug & play)	Simple commissioning/diagnostic routines using PC tools
	MMC memory card	Data backup by simply replacing
Requirement-optimized operating behavior		
	Voltage/frequency characteristic for constant and square-law torque	Basic open-loop control technique for centrifugal pumps, fans and radial compressors with low requirements on the dynamic performance
	Encoderless vector control	Field-oriented control technique for reciprocating pumps/compressors with high requirements on the dynamic performance
Extended number of inputs/outputs – for flexible use in a wide range of applications		
	- Electrically isolated digital inputs (own potential group) - Isolated analog inputs	- Avoidance of parasitic voltages - EMC-compliant installation without additional components corresponding to the requirements of the process industry
	Direct connection of two resistance thermometers NI1000 / PT1000	Connection of temperature sensors without separate evaluation
	Motor temperature monitoring	Motor protection by directly connecting thermistors or bimetallic sensors
	Digital outputs with 230 V relay	Direct control of auxiliary equipment, e.g. actuator drives for flaps or valves

	Function	Benefit
Innovative functions		
	■ Automatic restart	■ Automatic acknowledgment of the fault after a power failure and automatic restart
	■ Flying restart	■ Synchronization of the inverter to a motor that is still rotating
	■ Skip frequencies	■ Resonance points of the mechanical system and piping can be skipped
	■ Load torque monitoring	■ Monitoring of the drive for dry running protection, blocked protection and belt monitoring
	■ Real-time clock	■ Precise time stamp for fault and alarm logging, buffer time of up to 5 days
	■ 3 freely programmable digital time switches	■ Three selectable events can be controlled as a function of the weekday / hour / minute
	■ Display of the energy consumption	■ Display of the electrical energy used ■ Display of the energy saved when compared to a control with throttle valve
	■ Free function blocks	■ Flexible use of integrated functions for optimum use in building technology, additional, external components can be eliminated
	■ PID controller	■ Closed-loop drive speed control as a function of process variables such as temperature, pressure, flow, air quality
	■ Bypass	■ Automatic switchover to line operation for faults or when the rated speed is reached
	■ Cascading drives	■ Energy-efficient adaptation of the flow rate by switching in/switching out up to three fixed-speed drives
Communication interfaces – simple and direct integration into the automation environment		
	■ Different communication interfaces • RS485 with USS protocol • Modbus RTU, BACNet MS/TP • Siemens FLN P1 • PROFIBUS DP • CANopen	■ Simple integration into building management systems, process control systems and automation systems
	■ External 24 V power supply	■ Bus is not interrupted when the inverter is in the off state
Special functions for optimum use in building technology		
	■ 3 additional, integrated, freely programmable PID controllers	■ Distributed control of flaps, heating and cooling valves without any additional control
	■ Multi-zone closed-loop control	■ Control of pressure, temperature, air quality in up to three zones (average value, minimum, maximum) with a setpoint that can be switched over
	■ Extended operation in the case of fire (essential service mode)	■ Maximum operating time of the drive in case of fire by changing the setpoints, suppressing faults and automatic restart

Mechanical data		
Degree of protection	Max. IP55 / UL Type 12	IP20 / UL Open Type
Electrical data		
Power rating (low overload LO)	0.37 ... 90 kW	0.37 ... 75 kW
Rated output current (low overload LO)	1.3 ... 178 A	1.3 ... 145 A
Line supply voltage	3 AC 380 ... 480 V ±10 %	
Line frequency	47 ... 63 Hz	
Overload capability (low overload LO / high overload HO)	Low Overload (LO): 150 % for 3 s plus 110 % for 57 s within a duty cycle of 300 s. High Overload (HO): 200 % for 3 s plus 150 % for 57 s within a duty cycle of 300 s. When using the overload capability, the continuous output current is not reduced.*	
Operating temperature	0 °C to +60 °C (122 °F) for power derating	
Relative humidity	< 95 % RH, condensation not permissible	
Output frequency	0 ... 650 Hz	
Digital/analog inputs and outputs	6DI/3DO/4AI/2AO	
Communication		
Bus interface	RS485/USS/Modbus RTU, BACnet MS/TP, Siemens FLN P1, PROFIBUS DP, CANopen	
Commissioning tools		
Software operator unit	STARTER for the commissioning PC	
Functions		
Open-loop/closed-loop control techniques	V/f (linear, square-law, FCC, ECO), sensorless vector control (SLVC)	
Protection functions	Motor temperature monitoring with and without temperature sensor (via PTC, KTY and ThermoClick sensor) ■ Overcurrent protection ■ Torque monitoring ■ Overvoltage protection (Vdc_max controller)	
Brake functions	DC brake	
Motors that can be connected	3-phase induction motors	
Standards		
Conformance with standards	UL, CE, c-tick	
Electromagnetic compatibility	Integrated line filter for installations acc. to EN 61800-3 Category C1 (filter class B) and EN 61800-3 Category C2 (filter class A)	

*Reduced overload cycle for PM230 IP20 from 22 kW (HO and LO), refer to the documentation for details

SINAMICS G120P: Configuration in three steps

1. Power Module



1. PM230 Power Module in IP55, IP20 degree of protection



2. Control Unit



2. CU230P-2 Control Unit (PROFIBUS DP, HVAC, CANopen)



3. Panel



3. BOP-2 / IOP operator panel or blanking cover

The SINAMICS G120P inverter comprises the PM230 Power Module, CU230P-2 Control Unit as well as an operator panel (IOP or BOP-2) or a blanking cover. When ordering, an order number is specified for each of the components. The order numbers are listed on the last page.

Selection and ordering data

Power Modules PM230 IP55 / IP20					
Rated power (LO)		Rated output current _{IN_LO}	Frame size	PM230 IP55 degree of protection, order number	PM230 IP20 degree of protection *, order number
kW	hp	A			
0.37	0.5	1.3	FSA	6SL3223-0DE13-7□A0	6SL3210-1NE11-3□L0
0.55	0.75	1.7		6SL3223-0DE15-5□A0	6SL3210-1NE11-7□L0
0.75	1.0	2.2		6SL3223-0DE17-5□A0	6SL3210-1NE12-2□L0
1.1	1.5	3.1		6SL3223-0DE21-1□A0	6SL3210-1NE13-1□L0
1.5	2.0	4.1		6SL3223-0DE21-5□A0	6SL3210-1NE14-1□L0
2.2	3.0	5.9		6SL3223-0DE22-2□A0	6SL3210-1NE15-8□L0
3.0	4.0	7.7		6SL3223-0DE23-0□A0	6SL3210-1NE17-7□L0
4.0	5.0	10.2	FSB	6SL3223-0DE24-0□A0	6SL3210-1NE21-0□L0
5.5	7.5	13.2		6SL3223-0DE25-5□A0	6SL3210-1NE21-3□L0
7.5	10	18		6SL3223-0DE27-5□A0	6SL3210-1NE21-8□L0
11.0	15	26	FSC	6SL3223-0DE31-1□A0	6SL3210-1NE22-6□L0
15.0	20	32		6SL3223-0DE31-5□A0	6SL3210-1NE23-2□L0
18.5	25	38		6SL3223-0DE31-8AA0	6SL3210-1NE23-8□L0
18.5	25	38	FSD	6SL3223-0DE31-8BA0	–
22	30	45		6SL3223-0DE32-2□A0	6SL3210-1NE24-5□L0
30	40	60		6SL3223-0DE33-0□A0	6SL3210-1NE26-0□L0
37	50	75	FSE	6SL3223-0DE33-7□A0	6SL3210-1NE27-5□L0
45	60	90		6SL3223-0DE34-5□A0	6SL3210-1NE28-8□L0
55	75	110	FSF	6SL3223-0DE35-5□A0	6SL3210-1NE31-1□L0
75	100	145		6SL3223-0DE37-5□A0	6SL3210-1NE31-5□L0
90	125	178		6SL3223-0DE38-8□A0	–

Integrated line filter

Non-filtered	-----	↑	U
Class A (for TN line supplies)	-----	A	A
Class B (for TN line supplies)	-----	B	

* PM230 IP20 from 22 kW: can be ordered from June 2012 onwards

Control Units		
Brief designation	Communication	Order number
CU230P-2 HVAC	RS485 / USS / Modbus RTU / BACnet MS / TP / Siemens FLN P1	6SL3243-0BB30-1HA2
CU230P-2 DP	PROFIBUS DP	6SL3243-0BB30-1PA2
CU230P-2 CAN	CANopen	6SL3243-0BB30-1CA2

Accessories	
Designation	Order number
IOP	6SL3255-0AA00-4JA0
BOP-2	6SL3255-0AA00-4CA1
Door mounting kit for IOP/BOP-2	6SL3256-0AP00-0JA0
Blanking cover for PM230 IP55 / UL Type 12	6SL3256-1BA00-0AA0
PC connection kit 2 for CU230P-2	6SL3255-0AA00-2CA0
Shield connection kit 1 for CU230P-2 IP20 HVAC / DP / CAN	6SL3264-1EA00-0FA0
MMC memory card 64 MB	6SL3054-4AG00-0AA0
SINAMICS documentation DVD	6SL30974CA000YGO

Frame size	Filters	Dimensions, G120P, degree of protection IP55**	Dimensions G120P, degree of protection IP20**
FSA	Unfiltered/filtered	154 x 460 x 264 / 6.06 x 18.11 x 9.8	73 x 196 x 248 / 2.87 x 7.72 x 9.37
FSB	Unfiltered/filtered	180 x 540 x 264 / 7.08 x 21.25 x 9.8	100 x 292 x 248 / 3.94 x 11.5 x 9.37
FSC	Unfiltered/filtered	230 x 620 x 264 / 9.05 x 24.40 x 9.8	140 x 355 x 248 / 5.51 x 13.98 x 9.37
FSD	Non-filtered	320 x 640 x 344 / 12.59 x 25.18 x 12.94	275 x 419 x 287 / 10.83 x 16.5 x 11.30
	Filtered		275 x 512 x 287 / 10.83 x 20.16 x 11.30
FSE	Non-filtered	320 x 751 x 344 / 12.59 x 29.55 x 12.94	275 x 499 x 287 / 10.83 x 19.65 x 11.30
	Filtered		275 x 635 x 287 / 10.83 x 25 x 11.30
FSF	Non-filtered	410 x 915 x 431 / 16.14 x 36.02 x 16.38	350 x 634 x 399 / 13.78 x 24.96 x 15.71
	Filtered		350 x 934 x 399 / 13.78 x 36.77 x 15.71

**Dimensions in mm / inch, max. W x H x D. The depth is specified with Control Unit and IOP.

Siemens AG
Industry Sector
Motion Control Systems
P.O. Box 3180
91050 ERLANGEN
GERMANY

Subject to change without prior notice
03/12
Order No.: E80001-A390-P210-X-7600
DISPO 21500
SCHÖ/40125 GD.MC.GM.SIPR.52.2.07
SB 04125.0
Printed in Germany
© Siemens AG 2012

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

All product designations may be trademarks or product names of Siemens AG or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.